

## Standard Flange Gasket Part Numbering

| Standard Flange Part Number                 |                 |                |                 |           |                                |  |
|---|-----------------|----------------|-----------------|-----------|--------------------------------|--|
| First Character                             | Pressure Class  | NPS            | Gasket Type     | Thickness | Material Code                  |  |
| G = Gasket                                  | 1=150           | .25 = ¼ inch   | R = RING GASKET | 06 = 1/16 | NA101 = NA1001                 | Soft gaskets are almost always 150 or 300 PC |
|   | 3=300           | 1.5 = 1 ½ inch | FF = FULL FACE  | 12 = 1/8  | E60G = EPDM                    | Spiral wounds are more common with higher PC |
|   | 4=400           | 10. = 10 inch  |                 | 25 = 1/4  | (See Material reference sheet) |  |
|   | 6=600           | 25. = 25 inch  |                 |           |                                |  |
|   | 9=900           |                |                 |           |                                |  |
|   | X=1500          |                |                 |           |                                | 10" or smaller NPS generally use 1/16" thick |
|   | Y=2500          |                |                 |           |                                | Above 10" NPS generally use 1/8" thick       |
|   | A=300/400/600   |                |                 |           |                                |  |
|   | B=900/1500      |                |                 |           |                                |  |
|   | <b>Examples</b> |                |                 |           |                                |  |
| <b>G1-2.0FF-12NA101</b>                     |                 |                |                 |           |                                |  |
| 150 PC, 2" NPS, 1/8" thick, NA1001 material |                 |                |                 |           |                                |  |
| <b>G3-10.R-25E60G</b>                       |                 |                |                 |           |                                |  |
| 300 PC, 10" NPS, 1/4" thick, EPDM           |                 |                |                 |           |                                |  |